

**EBOX-3330 Series 2GB RAM, VGA, LAN x 1, RS-232**

Model Type		EB-3332-SS	EB-3332-C1	EB-3332-C2	EB-3332-C3	EB-3332-C4
Processor		Vortex86DX2 (933MHz)				
BIOS		AMI BIOS				
Memory		Onboard 2GB DDR2				
VGA		Integrated Graphics Chip/ D-Sub 15-pin				
Ethernet		10/100 Mbps LAN x 1 (RJ-45 connector, Built-in PXE diskless boot)				
USB (2.0)		External: 3 ports (Front x 2, Rear x 1) Internal: 1 port				
HD Audio		Line out				
I/O	SD Slot	1x				
	SATA	1x				
	COM1	N/A	RS-232	RS-232	RS-232	RS-232
	COM2		N/A	RS-232	RS-232	RS-232
	COM3			N/A	RS-232	RS-232
	COM4				N/A	N/A
Auto Power On		Yes				
Power		DC +8V ~ +15V				
Dimensions		115 x 115 x 35 mm				
Weight		500g				
Operation Temp.		5 ~ 50 °C				
Certification		CE, FCC				

**Optional:**

1. Mic input
2. Internal SD Card slot
3. TTL Level RS-232

**EBOX-3330 Series 2GB RAM, VGA, LAN x 1, RS-485**

Model Type	EB-3332-851	EB-3332-852	EB-3332-851C1	EB-3332-851C2	EB-3332-851C3	EB-3332-852C1	EB-3332-852C2	EB-3332-851221	EB-3332-851221C1	EB-3332-851221C2	
Processor	Vortex86DX2 (933MHz)										
BIOS	AMI BIOS										
Memory	Onboard 2GB DDR2										
VGA	Integrated Graphics Chip/ D-Sub 15-pin										
Ethernet	10/100 Mbps LAN x 1 (RJ-45 connector, Built-in PXE diskless boot)										
USB (2.0)	External: 3 ports (Front x 2, Rear x 1) Internal: 1 port										
HD Audio	Line out										
I/O	SD Slot	1x									
	SATA	1x									
	COM1	RS-485	RS-485	RS-485	RS-485	RS-485	RS-485	RS-485	RS-485	RS-485	RS-485
	COM2	N/A	RS-485	RS-232	RS-232	RS-232	RS-485	RS-485	RS-422	RS-422	RS-422
	COM3		N/A	N/A	RS-232	RS-232	RS-232	RS-232	N/A	RS-232	RS-232
COM4	N/A	RS-232			N/A	RS-232	N/A	RS-232			
Auto Power On	Yes										
Power	DC +8V ~ +15V										
Dimensions	115 x 115 x 35 mm										
Weight	500g										
Operation Temp.	5 ~ 50 ℃										
Certification	CE, FCC										

**Optional:**

1. Mic input
2. Internal SD Card slot
3. TTL Level RS-232

**EBOX-3330 Series 2GB RAM, VGA, LAN x 1, RS-422**

Model Type	EB-3332-221	EB-3332-222	EB-3332-221C1	EB-3332-221C2	EB-3332-221C3	EB-3332-222C1	EB-3332-222C2
Processor	Vortex86DX2 (933MHz)						
BIOS	AMI BIOS						
Memory	Onboard 2GB DDR2						
VGA	Integrated Graphics Chip/ D-Sub 15-pin						
Ethernet	10/100 Mbps LAN x 1 (RJ-45 connector, Built-in PXE diskless boot)						
USB (2.0)	External: 3 ports (Front x 2, Rear x 1) Internal: 1 port						
HD Audio	Line out						
I/O	SD Slot	1x					
	SATA	1					
	COM1	RS-422	RS-422	RS-422	RS-422	RS-422	RS-422
	COM2	N/A	RS-422	RS-232	RS-232	RS-232	RS-422
	COM3		N/A	N/A	RS-232	RS-232	RS-232
COM4				N/A	RS-232	N/A	
Auto Power On	Yes						
Power	DC +8V ~ +15V						
Dimensions	115 x 115 x 35 mm						
Weight	500g						
Operation Temp.	5 ~ 50 °C						
Certification	CE, FCC						

**Optional:**

1. Mic input
2. Internal SD Card slot
3. TTL Level RS-232

**EBOX-3330 Series 2GB RAM, VGA, LAN x 2, RS-232**

Model Type		EB-3332-L2SS	EB-3332-L2C1	EB-3332-L2C2	EB-3332-L2C3	EB-3332-L2C4
Processor		Vortex86DX2 (933MHz)				
BIOS		AMI BIOS				
Memory		Onboard 2GB DDR2				
VGA		Integrated Graphics Chip/ D-Sub 15-pin				
Ethernet		10/100 Mbps LAN x 1, 1G LAN x 1 (RJ-45 connector, Built-in PXE diskless boot)				
USB (2.0)		External: 3 ports (Front x 2, Rear x 1) Internal: 1 port				
HD Audio		Line out				
I/O	SD Slot	1x				
	SATA	1x				
	COM1	N/A	RS-232	RS-232	RS-232	RS-232
	COM2		N/A	RS-232	RS-232	RS-232
	COM3	N/A		N/A	RS-232	RS-232
	COM4			N/A	N/A	RS-232
Auto Power On		Yes				
Power		DC +8V ~ +15V				
Dimensions		115 x 115 x 35 mm				
Weight		500g				
Operation Temp.		5 ~ 50 °C				
Certification		CE, FCC				

**Optional:**

1. Mic input
2. Internal SD Card slot
3. TTL Level RS-232

**EBOX-3330 Series 2GB RAM, VGA, LAN x 2, RS-485**

Model Type	EB-3332-L2851	EB-3332-L2852	EB-3332-L2851C1	EB-3332-L2851C2	EB-3332-L2851C3	EB-3332-L2852C1	EB-3332-L2852C2	EB-3332-L2851221	3332-L2851221C1	3332-L2851221C2		
Processor	Vortex86DX2 (933MHz)											
BIOS	AMI BIOS											
Memory	Onboard 2GB DDR2											
VGA	Integrated Graphics Chip/ D-Sub 15-pin											
Ethernet	10/100 Mbps LAN x 1, 1G LAN x 1 (RJ-45 connector, Built-in PXE diskless boot)											
USB (2.0)	External: 3 ports (Front x 2, Rear x 1) Internal: 1 port											
HD Audio	Line out											
I/O	SD Slot	1x										
	SATA	1x										
	COM1	RS-485	RS-485	RS-485	RS-485	RS-485	RS-485	RS-485	RS-485	RS-485	RS-485	
	COM2	N/A	RS-485	RS-232	RS-232	RS-232	RS-232	RS-485	RS-485	RS-422	RS-422	RS-422
	COM3		N/A	N/A	RS-232	RS-232	RS-232	RS-232	N/A	RS-232	RS-232	
	COM4				N/A	RS-232	N/A	RS-232		N/A	RS-232	
Auto Power On	Yes											
Power	DC +8V ~ +15V											
Dimensions	115 x 115 x 35 mm											
Weight	500g											
Operation Temp.	5 ~ 50 °C											
Certification	CE, FCC											

**Optional:**

1. Mic input
2. Internal SD Card slot
3. TTL Level RS-232

**EBOX-3330 Series 2GB RAM, VGA, LAN x 2, RS-422**

Model Type	EB-3332-L2221	EB-3332-L2222	EB-3332-L2221C1	EB-3332-L2221C2	EBO3332-L2221C3	EB-3332-L2222C1	EB-3332-L2222C2
Processor	Vortex86DX2 (933MHz)						
BIOS	AMI BIOS						
Memory	Onboard 2GB DDR2						
VGA	Integrated Graphics Chip/ D-Sub 15-pin						
Ethernet	10/100 Mbps LAN x 1, 1G LAN x 1 (RJ-45 connector, Built-in PXE diskless boot)						
USB (2.0)	External: 3 ports (Front x 2, Rear x 1) Internal: 1 port						
HD Audio	Line out						
I/O	SD Slot	1x					
	SATA	1x					
	COM1	RS-422	RS-422	RS-422	RS-422	RS-422	RS-422
	COM2	N/A	RS-422	RS-232	RS-232	RS-232	RS-422
	COM3		N/A	N/A	RS-232	RS-232	RS-232
	COM4			N/A	RS-232	RS-232	RS-232
Auto Power On	Yes						
Power	DC +8V ~ +15V						
Dimensions	115 x 115 x 35 mm						
Weight	500g						
Operation Temp.	5 ~ 50 °C						
Certification	CE, FCC						

**Optional:**

1. Mic input
2. Internal SD Card slot
3. TTL Level RS-232

**EBOX-3330 Series 2GB RAM, HDMI, LAN x 1, RS-232**

Model Type	EB-3332-SSDMI	EB-3332-C1DMI	EB-3332-C2DMI	EB-3332-C3DMI	EB-3332-C4DMI
Processor	Vortex86DX2 (933MHz)				
BIOS	AMI BIOS				
Memory	Onboard 2GB DDR2				
VGA	HDMI				
Ethernet	10/100 Mbps LAN x 1 (RJ-45 connector, Built-in PXE diskless boot)				
USB (2.0)	External: 3 ports (Front x 2, Rear x 1) Internal: 1 port				
HD Audio	Mic in				
I/O	PS2	PS/2 for Keyboard / Mouse x 1			
	SD Slot	1x			
	SATA	1x			
	COM1	RS-232	RS-232	RS-232	RS-232
	COM2	N/A	RS-232	RS-232	RS-232
	COM3		N/A	N/A	RS-232
	COM4			N/A	RS-232
Auto Power On	Yes				
Power	DC +8V ~ +15V				
Dimensions	115 x 115 x 35 mm				
Weight	500g				
Operation Temp.	5 ~ 50 °C				
Certification	CE, FCC				

**Optional:**

1. Mic input
2. Internal SD Card slot
3. TTL Level RS-232

**EBOX-3330 Series 2GB RAM, HDMI, LAN x 1, RS-485**

Model Type	EB-3332-851DMI	EB-3332-852DMI	EB-3332-851C1DMI	EB-3332-851C2DMI	EB-3332-851C3DMI	EB-3332-852C1DMI	EB-3332-852C2DMI	3332-851221DMI	3332-851221C1DMI	3332-851221C2DMI		
Processor	Vortex86DX2 (933MHz)											
BIOS	AMI BIOS											
Memory	Onboard 2GB DDR2											
VGA	HDMI											
Ethernet	1G LAN x 1 (RJ-45 connector, Built-in PXE diskless boot)											
USB (2.0)	External: 3 ports (Front x 2, Rear x 1) Internal: 1 port											
HD Audio	Mic in											
I/O	PS2	PS/2 for Keyboard / Mouse x 1										
	SD Slot	1x										
	SATA	1x										
	COM1	RS-485	RS-485	RS-485	RS-485	RS-485	RS-485	RS-485	RS-485	RS-485	RS-485	
	COM2	N/A	RS-485	RS-232	RS-232	RS-232	RS-232	RS-485	RS-485	RS-422	RS-422	RS-422
	COM3		N/A	N/A	RS-232	RS-232	RS-232	RS-232	N/A	RS-232	RS-232	
	COM4				N/A	RS-232	N/A	RS-232		N/A	RS-232	
Auto Power On	Yes											
Power	DC +8V ~ +15V											
Dimensions	115 x 115 x 35 mm											
Weight	500g											
Operation Temp.	5 ~ 50 °C											
Certification	CE, FCC											

**Optional:**

1. Mic input
2. Internal SD Card slot
3. TTL Level RS-232



**EBOX-3330 Series 2GB RAM, HDMI, LAN x 1, RS-422**

Model Type	EB-3332-221DMI	EB-3332-222DMI	EB-3332-221C1DMI	EB-3332-221C2DMI	EB-3332-221C3DMI	EB-3332-222C1DMI	EB-3332-222C2DMI
Processor	Vortex86DX2 (933MHz)						
BIOS	AMI BIOS						
Memory	Onboard 2GB DDR2						
VGA	HDMI						
Ethernet	10/100 LAN x 1 (RJ-45 connector, Built-in PXE diskless boot)						
USB (2.0)	External: 3 ports (Front x 2, Rear x 1) Internal: 1 port						
HD Audio	Mic in						
I/O	PS2	PS/2 for Keyboard / Mouse x 1					
	SD Slot	1x					
	SATA	1x					
	COM1	RS-422	RS-422	RS-422	RS-422	RS-422	RS-422
	COM2	N/A	RS-422	RS-232	RS-232	RS-232	RS-422
	COM3		N/A	N/A	RS-232	RS-232	RS-232
	COM4		N/A	N/A	N/A	RS-232	N/A
Auto Power On	Yes						
Power	DC +8V ~ +15V						
Dimensions	115 x 115 x 35 mm						
Weight	500g						
Operation Temp.	5 ~ 50 °C						
Certification	CE, FCC						

**Optional:**

1. Mic input
2. Internal SD Card slot
3. TTL Level RS-232

**EBOX-3330 Series 2GB RAM, HDMI, LAN x 2, RS-232**

Model Type	EB-3332-L2SSDMI	EB-3332-L2C1DMI	EB-3332-L2C2DMI	EB-3332-L2C3DMI	EB-3332-L2C4DMI	
Processor	Vortex86DX2 (933MHz)					
BIOS	AMI BIOS					
Memory	Onboard 2GB DDR2					
VGA	HDMI					
Ethernet	10/100 Mbps LAN x 1, 1G LAN x 1 (RJ-45 connector, Built-in PXE diskless boot)					
USB (2.0)	External: 3 ports (Front x 2, Rear x 1) Internal: 1 port					
HD Audio	Mic in					
I/O	PS2	PS/2 for Keyboard / Mouse x 1				
	SD Slot	1x				
	SATA	1x				
	COM1	N/A	RS-232	RS-232	RS-232	RS-232
	COM2		N/A	RS-232	RS-232	RS-232
	COM3			N/A	N/A	RS-232
	COM4		N/A		N/A	RS-232
Auto Power On	Yes					
Power	DC +8V ~ +15V					
Dimensions	115 x 115 x 35 mm					
Weight	500g					
Operation Temp.	5 ~ 50 °C					
Certification	CE, FCC					

**Optional:**

1. Mic input
2. Internal SD Card slot
3. TTL Level RS-232

**EBOX-3330 Series 2GB RAM, HDMI, LAN x 2, RS-485**

Model Type	EB-3332-L2851DMI	EB-3332-L2852DMI	3332-L2851C1DMI	3332-L2851C2DMI	3332-L2851C3DMI	3332-L2852C1DMI	3332-L2852C2DMI	3332-L2851221DMI	3332-L2851221C1D	3332-L2851221C2D		
Processor	Vortex86DX2 (933MHz)											
BIOS	AMI BIOS											
Memory	Onboard 2GB DDR2											
VGA	HDMI											
Ethernet	10/100 Mbps LAN x 1, 1G LAN x 1 (RJ-45 connector, Built-in PXE diskless boot)											
USB (2.0)	External: 3 ports (Front x 2, Rear x 1) Internal: 1 port											
HD Audio	Mic in											
I/O	PS2	PS/2 for Keyboard / Mouse x 1										
	SD Slot	1x										
	SATA	1x										
	COM1	RS-485	RS-485	RS-485	RS-485	RS-485	RS-485	RS-485	RS-485	RS-485	RS-485	
	COM2	N/A	RS-485	RS-232	RS-232	RS-232	RS-232	RS-485	RS-485	RS-422	RS-422	RS-422
	COM3		N/A	N/A	RS-232	RS-232	RS-232	RS-232	RS-232	N/A	RS-232	RS-232
	COM4				N/A	RS-232	N/A	RS-232	N/A		RS-232	N/A
Auto Power On	Yes											
Power	DC +8V ~ +15V											
Dimensions	115 x 115 x 35 mm											
Weight	500g											
Operation Temp.	5 ~ 50 °C											
Certification	CE, FCC											

**Optional:**

1. Mic input
2. Internal SD Card slot
3. TTL Level RS-232

**EBOX-3330 Series 2GB RAM, HDMI, LAN x 2, RS-422**

Model Type	EB-3332-L2221DMI	EB-3332-L2222DMI	3332-L2221C1DMI	3332-L2221C2DMI	3332-L2221C3DMI	3332-L2222C1DMI	3332-L2222C2DMI
Processor	Vortex86DX2 (933MHz)						
BIOS	AMI BIOS						
Memory	Onboard 2GB DDR2						
VGA	HDMI						
Ethernet	10/100 LAN x 1, 1G LAN x 1 (RJ-45 connector, Built-in PXE diskless boot)						
USB (2.0)	External: 3 ports (Front x 2, Rear x 1) Internal: 1 port						
HD Audio	Mic in						
I/O	PS2	PS/2 for Keyboard / Mouse x 1					
	SD Slot	1x					
	SATA	1x					
	COM1	RS-422	RS-422	RS-422	RS-422	RS-422	RS-422
	COM2	N/A	RS-422	RS-232	RS-232	RS-232	RS-422
	COM3		N/A	N/A	RS-232	RS-232	RS-232
	COM4			N/A	N/A	RS-232	N/A
Auto Power On	Yes						
Power	DC +8V ~ +15V						
Dimensions	115 x 115 x 35 mm						
Weight	500g						
Operation Temp.	5 ~ 50 °C						
Certification	CE, FCC						

**Optional:**

1. Mic input
2. Internal SD Card slot
3. TTL Level RS-232