

DIN PG-333x Series

Model Type	D-3330-SS	D-3330-C1851	D-3330-C2	D-3330-C4	D-3330-851221	D-3330-851221C2	D-3330-852	D-3330-852C2	D-3330-221C1	D-3330-222	D-3330-222C2	
	D-3332-SS	D-3332-C1851	D-3332-C2	D-3332-C4	D-3332-851221	D-3332-851221C2	D-3332-852	D-3332-852C2	D-3332-221C1	D-3332-222	D-3332-222C2	
Processor	Vortex86DX2 (933MHz)											
BIOS	AMI BIOS											
Memory	Onboard 1GB DDR2 for 3330 Series/ Onboard 2GB DDR2 for 3332 Series											
VGA	Integrated Graphics Chip/ D-Sub 15-pin											
Ethernet	10/100 Mbps LAN x 1, 1G LAN x 1 (RJ-45 connector, Built-in PXE diskless boot)											
USB (2.0)	External: 2 ports (Front x 2) Internal: 1 port (space reserved dimension 33 x 20 mm)											
I/O	SD Slot	1x (Internal)										
	SATA	1x										
	COM1	N/A	RS-232	RS-232	RS-232	RS-485	RS-485	RS-485	RS-485	RS-422	RS-422	RS-422
	COM2		RS-485	RS-232	RS-232	RS-422	RS-422	RS-485	RS-485	RS-232	RS-422	RS-422
	COM5		N/A	N/A	RS-232	N/A	RS-232	N/A	RS-232	N/A	N/A	RS-232
COM6	N/A		N/A	RS-232	RS-232		RS-232					
Auto Power On	Yes											
Power	DC +8V ~ +15V (Pluggable Terminal Block 3-Pin 5.00 mm Pitch)											
Dimensions	152 x 104 x 54 mm											
Unit Net Weight	760g											
Operation Temp.	5 ~ 50 °C											
Certifications	CE, FCC, VCCI, Vibration											
Optional	1. Mic input/ Line out 2. TTL Level RS-232											
Note	RS-232 COM ports in Full 9pin											

Features:

- DIN rail mounting support
- Vortex86DX2 (933MHz)
- Onboard 1GB/ 2GB DDR2
- PXE Diskless Boot
- 10/100 Mbps LAN x 1, 1Gbps LAN x 1
- USB V2.0 port x 3
- SD, SDHC support (Internal)
- SATA DOM support (Internal)
- RS-232 Up to 4 ports (Optional)
- RS-485 Up to 2 ports (Optional)
- RS-422 Up to 2 ports (Optional)
- WiFi Dongle support (Optional)
- Auto Power On support
- Pluggable Terminal Block (3-Pin 5.00 mm Pitch)

